



CYCLONE RATED





















SUNTUF The Original and still the best

Welcome to the Suntuf range of polycarbonate sheeting.

The SUNTUF range is available in 3 great styles - Standard, SolarSmart and SolarSmart Selective

SUNTUF Your First Choice

- 1st polycarbonate sheet in Australia
- 1st to introduce anti glare technology
- The only company able to emboss sheets
- 1st with solar control
- 1st with SolarSmart near infra red technology

- 1st cyclonically rated sheet
- 1st to introduce Lifetime Warranty
- 1st to introduce 25 year Water **Tight Warranty**
- Only Suntuf is proven for over 25 years

Certification

- Limited Lifetime Warranty
- 99.9% UV Protection
- Australian Standards Certified (AS4256-5)
- Early Fire Hazard Test (tested to AS1530)
- Sandbag Impact Test (tested to AS1562-3)
- Rated for cyclonic winds (tested to AS4040.3)

SOLARSMART® Premium Heat Reduction Sheeting

SolarSmart Premium Sheeting

SolarSmart reflects more heat across the entire ultraviolet light spectrum, not just the portion that provides visible light. "Near infra-red" radiation from the sun is invisible to our eyes but contains large amounts of heat that we feel on our skin. SolarSmart is unique in its ability to block out "near infra red" heat radiation. Hold up a sample to the sun or to an ultraviolet lamp and you will feel the SolarSmart difference.

- Proven over 25 years in Australia
- Minimal glare
- High quality
- Natural diffused light
- Offers year round protection
- Natural colour range providing natural light
- Unique embossed finish



COMPARISON CHART





SUNTUF Polycarbonate Sheeting Comparison Chart

Standard	Comment		Light Transmiss	ion	Heat* Transmission		Comfort Level		evel
Clear	Maximum light & heat		90%)	86%				
Cedar Bronze	Direct light / darker bronze tint		25%)	48%				
Solar Grey	Direct light / natural grey tint		20%)	43%				
opal (Diffused light / good shading		45%)	40%				
Smooth Cream	Soft light & low glare	Soft light & low glare)	33%				
SolarSmart									
Transparent Grey	Semi-diffused light / low glare		20%		30%				
Diffused Ice	Diffused light / low glare		48%		21%				
Diffused Grey	Diffused light / low glare		20%)	18%				
SolarSmart Selective									
Sandune	Maximum heat reduct	15%)	15%					
Metallic Jasper	Maximum heat reduct	15%)	16%					
*Percentage of direct heat from the sun passing through the sheet.									
	Standard Clear Cedar Bronze Solar Grey Opal	SolarSmart Diffused Grey Diffused Ice Transparent Grey	SolarSmart Selective Sandune Metallic Jasper	Width (mm)	Coverage (mm)	Height (mm)	Thickness (mm)	Weight (kg/m²)	Min. Cold Bending Radius (mm)
Transparent Sheets		•					•		
Translucent Sheets	•								
Corregated									
		• • •	• •	860	760	17	0.8	1.1	4000
Greca							_		
	• • • •	• • •	• •	810	760	16	0.8	1.2	4000
Sheet Lengths (mm) 1800	2100 2400	2700 3000	3600	4200	4800	54	00	6000	7200

For Span and Installation details visit www.palram.com.au Trimdeck/TL5 1mm, SPANTUF and KINGKLIP are available for viewing on our website.

ACCESSORIES



 $\hbox{* Clearfix \& Polymate screws are the only recommended screws to be used with Palram's products.}\\$

PALRAM SA 517A Cross Keys Rd, Cavan 5094 Tel: 08 8262 2288

Fax: 08 8262 3388 salessa@palram.com.au

PALRAM NSW

196 Newton Rd, Wetherill Pk 2164 Tel: 02 9757 3166 Fax: 02 9756 1008 salesnsw@palram.com.au

PALRAM VIC

34b Randor St, Campbellfield 3061 Tel: 03 9357 9240 Fax: 03 9357 9270 salesvic@palram.com.au

PALRAM WA

74 Christable Way, Landsdale 6065 Tel: 08 9302 4173 Fax: 08 9302 5287 saleswa@palram.com.au

PALRAM QLD

30a Enterprise St, Richlands 4077 Tel: 07 3162 9111 Fax: 07 3161 7168 salesqld@palram.com.au

Inasmuch as PALRAM Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the materials suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be constituted as constituting a license under any PALRAM Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. PALRAM Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local PALRAM Industries supplier to ensure that you have obtained the most up to date information. Slight colour variation may occur between production runs. Colour depicted in brochure are only a representation. Refer to website for lifetime warranty and hail damage conditions.